


DIMENSIONS FOR ROADWAY SECTIONS

ROADWAY CLASSIFICATION	"A" RIGHT-OF-WAY	"B" ROADWAY WIDTH	"C" 1/2 PAVED SECTION	"D" ASPHALTIC CONCRETE SURFACE	"E" ASPHALTIC CONCRETE BINDER	"F" MINERAL AGGREGATE BASE	"G" CONCRETE CURB/ CURB AND GUTTER
				GRADING E (SEE NOTE 1 BELOW.)	GRADING B, C, OR B MODIFIED (SEE NOTE 2 BELOW.)	TYPE A (SEE NOTE 3 BELOW.)	
PRINCIPAL ARTERIAL	100'	84'	40'-6"	1.5"	3.5"	15"	TYPE A
MINOR ARTERIAL	80'	60'	28'-6"	1.5"	3.5"	15"	TYPE A
COLLECTOR STREET	60'	36'	16'-6"	1.5"	2.5"	8"	TYPE A
LOCAL STREET	50'	26'	11'-6"	1.5"	2.5"	8"	SEE NOTE 1 WITH TYPICAL SECTION.

1. ASPHALTIC CONCRETE SURFACE SHALL BE GRADING E, CITY OF CHATTANOOGA SPECIFICATIONS, CONTAINING AT LEAST 45% RIVER SAND.
 2. ASPHALTIC CONCRETE BINDER SHALL BE GRADING B MODIFIED OR GRADING C, CITY OF CHATTANOOGA SPECIFICATIONS; OR GRADING B, TENNESSEE D.O.T. SPECIFICATIONS.
 3. MINERAL AGGREGATE BASE SHALL BE COMPACTED 303-01, TYPE A, GRADING D ("33-P"), TENNESSEE D.O.T. SPECIFICATIONS.



F:\STDWGS\TypSection\typ-sec_2.dwg



1	REVISIONS AS MARKED OR CLOUDED	8/24/01
0	INITIAL ISSUE	12/10/99
NO.	REVISION	DATE

CITY OF CHATTANOOGA AND HAMILTON COUNTY	
<i>ROADWAY SECTIONS</i>	
DATE OF ORIGINAL ISSUE DECEMBER 10, 1999	STANDARD NUMBER : <i>SD-200.02</i>